

Class C



Ören Digital RG 6 U/6 (CCS/Cu)

Kullanım Alanları

Bina içi CATV dağıtım kablosu ve CCTV gibi düşük zayıflama istenen sistemlerde bağlantı kablosu olarak kullanılır.

Kablo Yapısı

İç İletken
Ø 1.02 mm CCS

İzolasyon
Ø 4.60 mm Fiziksel Köpüklü
Skin/Foam/Skin PE

1. Ekran
Cu-Pet Folyo

2. Ekran
Tavlı Bakır Tellerden Örgü

Dış Kılıf
Ø 6.80 mm PVC

Teknik Özellikler

Kablo Ağırlığı 45 kg/km
Min. Bük. Yarı Çapı 30 mm
Maks. Gergi Kuvveti 210 N
Çalışma Sıcaklığı -30 °C ... +70 °C
Ambalaj 100 / 300 / 500 m

Elektriksel Özellikler

Empedans 75 ± 3 Ω
Kapasitans 53 ± 2 pF/m
Yayıma Hızı % 84
Yalıtım Direnci > 2 GΩxkm
Çalışma Voltajı 1300 V
Test Voltajı 3000 V
İç İletken Direnci < 95.00 Ω/km

Zayıflamalar (20°C)

5 MHz 1.85 dB/100m
50 MHz 4.65 dB/100m
230 MHz 9.25 dB/100m
470 MHz 14.60 dB/100m
860 MHz 19.80 dB/100m
1000 MHz 21.60 dB/100m
1200 MHz 23.05 dB/100m
2150 MHz 32.40 dB/100m
3000 MHz 39.05 dB/100m

Geri Dönüş Kaybı (20°C)

5-470 MHz > 26 dB
470-1200 MHz > 23 dB
1200-2000 MHz > 20 dB
2000-3000 MHz > 18 dB

Transfer Empedansı

5-30 MHz ≤ 50 mΩ/m

Ekranlama Zayıflaması

30-1200 MHz ≥ 75 dB
1200-2000 MHz ≥ 65 dB
2000-3000 MHz ≥ 55 dB

Standartlar

Ekranlama Sınıfı Class C
EN 50117-2-4

CPR Sınıfı
E_{ca}

Alev Geciktiricilik
EN 60332-1-2

Application

These types of cables are used for CCTV and indoor CATV distributions and connections of systems which require low attenuations.

Cable Construction

Inner Conductor
Ø 1.02 mm CCS

Insulation
Ø 4.60 mm Gas Injected
Skin/Foam/Skin PE

1st Shielding
Cu-Pet Foil

2nd Shielding
Annealed Copper Wire Braiding

Outer Sheath
Ø 6.80 mm PVC

Technical Properties

Cable Weight 45 kg/km
Min. Bending Radius 30 mm
Max. Tensile Strength 210 N
Temperature Range -30 °C ... +70 °C
Packing 100 / 300 / 500 m

Electrical Properties

Impedance 75 ± 3 Ω
Capacitance 53 ± 2 pF/m
Velocity of Propagation 84 %
Insulation Resistance > 2 GΩxkm
Operating Voltage 1300 V
Test Voltage 3000 V
Inner Conductor DCR < 95.00 Ω/km

Attenuations (20°C)

5 MHz 1.85 dB/100m
50 MHz 4.65 dB/100m
230 MHz 9.25 dB/100m
470 MHz 14.60 dB/100m
860 MHz 19.80 dB/100m
1000 MHz 21.60 dB/100m
1200 MHz 23.05 dB/100m
2150 MHz 32.40 dB/100m
3000 MHz 39.05 dB/100m

Return Loss (20°C)

5-470 MHz > 26 dB
470-1200 MHz > 23 dB
1200-2000 MHz > 20 dB
2000-3000 MHz > 18 dB

Transfer Impedance

5-30 MHz ≤ 50 mΩ/m

Screening Attenuation


30-1200 MHz ≥ 75 dB
1200-2000 MHz ≥ 65 dB
2000-3000 MHz ≥ 55 dB

Standards

Screening Class Class C
EN 50117-2-4

Euro Class
E_{ca}

Flame Retardancy
EN 60332-1-2



Class C



Ören Digital RG 6 U/6 (CCS/Cu) HFFR

Kullanım Alanları

Bina içi CATV dağıtım kablosu ve CCTV gibi düşük zayıflama istenen sistemlerde bağlantı kablosu olarak kullanılır. Halogen Free Compound sayesinde, alev geciktirici özelliğe sahiptir. İnsan yoğunluğu fazla olan yapılarda bu tip HFFR özellikli kabloların kullanılması önerilmektedir.

Kablo Yapısı

İç İletken
Ø 1.02 mm CCS

İzolasyon
Ø 4.60 mm Fiziksel Köpüklü
Skin/Foam/Skin PE

1. Ekran
Cu-Pet Folyo

2. Ekran
Tavlı Bakır Tellerden Örgü

Dış Kılıf
Ø 6.80 mm HFFR*

Teknik Özellikler

Kablo Ağırlığı 46 kg/km
Min. Bük. Yarı Çapı 30 mm
Maks. Gergi Kuvveti 210 N
Çalışma Sıcaklığı -30 °C ... +70 °C
Ambalaj 100 / 300 / 500 m

Elektriksel Özellikler

Empedans 75 ± 3 Ω
Kapasitans 53 ± 2 pF/m
Yayımla Hızı % 84
Yalıtım Direnci > 2 GΩxkm
Çalışma Voltajı 1300 V
Test Voltajı 3000 V
İç İletken Direnci < 95.00 Ω/km

Zayıflamalar (20°C)

5 MHz 1.85 dB/100m
50 MHz 4.65 dB/100m
230 MHz 9.25 dB/100m
470 MHz 14.60 dB/100m
860 MHz 19.80 dB/100m
1000 MHz 21.60 dB/100m
1200 MHz 23.05 dB/100m
2150 MHz 32.40 dB/100m
3000 MHz 39.05 dB/100m

Geri Dönüş Kaybı (20°C)

5-470 MHz > 26 dB
470-1200 MHz > 23 dB
1200-2000 MHz > 20 dB
2000-3000 MHz > 18 dB

Transfer Empedansı

5-30 MHz ≤ 50 mΩ/m

Ekranlama Zayıflaması

30-1200 MHz ≥ 75 dB
1200-2000 MHz ≥ 65 dB
2000-3000 MHz ≥ 55 dB

Standartlar

Ekranlama Sınıfı Class C
EN 50117-2-4

CPR Sınıfı
D_{ca}

Alev Geciktiricilik
EN 60332-1-2

Korozif Gaz Testi
TS EN 60754-2

Duman Yoğunluğu
EN 61034-2

Application

These types of cables are used for CCTV and indoor CATV distributions and connections of systems which require low attenuations. These cables are Halogen Free, Non Corrosive and Flame retardant, thanks to the HFFR Compound that has been used on their construction.

Cable Construction

Inner Conductor
Ø 1.02 mm CCS

Insulation
Ø 4.60 mm Gas Injected
Skin/Foam/Skin PE

1st Shielding
Cu-Pet Foil

2nd Shielding
Annealed Copper Wire Braiding

Outer Sheath
Ø 6.80 mm HFFR*

Technical Properties

Cable Weight 46 kg/km
Min. Bending Radius 30 mm
Max. Tensile Strength 210 N
Temperature Range -30 °C ... +70 °C
Packing 100 / 300 / 500 m

Electrical Properties

Impedance 75 ± 3 Ω
Capacitance 53 ± 2 pF/m
Velocity of Propagation 84 %
Insulation Resistance > 2 GΩxkm
Operating Voltage 1300 V
Test Voltage 3000 V
Inner Conductor DCR < 95.00 Ω/km

Attenuations (20°C)

5 MHz 1.85 dB/100m
50 MHz 4.65 dB/100m
230 MHz 9.25 dB/100m
470 MHz 14.60 dB/100m
860 MHz 19.80 dB/100m
1000 MHz 21.60 dB/100m
1200 MHz 23.05 dB/100m
2150 MHz 32.40 dB/100m
3000 MHz 39.05 dB/100m

Return Loss (20°C)

5-470 MHz > 26 dB
470-1200 MHz > 23 dB
1200-2000 MHz > 20 dB
2000-3000 MHz > 18 dB

Transfer Impedance

5-30 MHz ≤ 50 mΩ/m

Screening Attenuation

30-1200 MHz ≥ 75 dB
1200-2000 MHz ≥ 65 dB
2000-3000 MHz ≥ 55 dB

Standards

Screening Class Class C
EN 50117-2-4

Euro Class
D_{ca}

Flame Retardancy
EN 60332-1-2

Corrosive Gases Test
TS EN 60754-2

Smoke Density
EN 61034-2