



EC1200 CAT 7A S/FTP LSZH C_{ca}



Application

10Base-T, 100Base-T, 1000Base-T, 10GBase-T, and Fibredbus systems. Applicable for Power over Ethernet PoE / PoE+

Cable Construction

- 22 AWG Bare Copper
- Skin/Foam/Skin PE Insulation
- Al-Pet Foil 100% Coverage
- Tinned Copper Wire Braiding
- Ø 7.90 mm ± 0.20 LSZH

Technical Properties

Cable Weight	72 kg/km
Copper Weight	30 kg/km
Min. Bending radius during draw in	62 mm
Min. Bending radius permanently installed	32 mm
Max. Tensile Strength	95 N
Min. Crush Resistance	1000 N/10 cm
Min. Impact	10 Impacts
Installation Temperature	0°C ... +50°C
Operating Temperature	-20°C ... +70°C
Packing	305 / 500 m

Electrical Properties

Max. Conductor Resistance	< 9.5 Ω / km
Max. Resistance Unbalance	< 2%
Min. Insulation Resistance	5000 MΩ x m
Mutual Capacitance	< 56 pF / m
Capacitance Unbalance	1600 pF / km
Impedance at 100 MHz	100 ± 5 Ω
Velocity of Propagation	76 %
Delay Skew	< 25 ns / 100 m
Coupling Attenuation	> 85 dB
Segregation Class	D
Transfer Impedance at 1/10/30 MHz	< 10/10/30 mΩ/m
Test Voltage	1000 V
Operating Voltage	125 V

at 20 °C

Standards

EIA/TIA-568
 ISO/IEC 11801 Class F
 IEC 61156-5, EN 50173-1
 EN 50288-4-1
 Euro Class
 C_{ca}, s1a, d2, a1
 Flame Retardancy
 EN 60332-1-2
 Corrosive Gases Test
 EN 50267-2-3
 Smoke Density
 EN 61034-2

Electrical Data (Nominal)

@ 20 °C

Frequency (MHz)	Attenuation (dB/100 m)	NEXT (dB)	PS - NEXT (dB)	ACR (dB/100 m)	PS-ACR (dB/100 m)	ACRF (dB/100 m)	PS-ACRF (dB/100 m)	Return Loss (dB)
1	1.9	101	101	99	96	101	98	24
4	3.2	101	101	97	94	98	95	30
10	4.9	98	98	95	92	98	95	32
100	17.2	97	97	82	79	84	81	34
250	28.0	93	92	63	60	70	67	27
500	41.5	95	92	56	53	61	58	24
600	43.7	88	85	45	42	59	56	22
800	53.2	84	81	30	27	52	49	20
1000	55.4	83	80	28	25	50	47	19
1200	57.0	80	77	23	20	49	46	18