



## EC200 Cat 5e U/UTP PVC E<sub>ca</sub>

### Application

10Base-T, 100Base-T, 1000Base-T systems. Applicable for Power over Ethernet (PoE) / PoE+

### Cable Construction

- 24 AWG Bare Copper
- PE Insulation
- Pair Separator
- Ø 5.10 ± 0.20 mm PVC

### Technical Properties

Cable Weight	38 kg/km
Copper Weight	16.3 kg/km
Min. Bending radius during draw in	50 mm
Min. Bending radius permanently installed	25 mm
Max. Tensile Strength	90 N
Min. Crush Resistance	1000 N/10 cm
Min. Impact	10 Impacts
Installation Temperature	0°C ... +50°C
Operating Temperature	-20°C ... +70°C
Packing	305 / 500 m

### Electrical Properties

Max. Conductor Resistance	< 9.5 Ω / km
Max. Resistance Unbalance	< 2%
Min. Insulation Resistance	5000 MΩ x m
Mutual Capacitance	< 60 pF / m
Capacitance Unbalance	1600 pF / km
Impedance at 100 MHz	100 ± 5 Ω
Velocity of Propagation	66 %
Delay Skew	< 45 ns / 100 m
Test Voltage	1000 V
Operating Voltage	125 V

at 20 °C

### Standards

EIA/TIA-568  
 ISO/IEC 11801 Class D  
 IEC 61156-5, EN 50173-1  
 EN 50288-3-1  
 Euro Class  
 E<sub>ca</sub>  
 Flame Retardancy  
 EN 60332-1-2

### Electrical Data (Nominal)

@ 20 °C

Frequency (MHz)	Attenuation (dB/100 m)	NEXT (dB)	PS - NEXT (dB)	ACR (dB/100 m)	PS-ACR (dB/100 m)	ACRF (dB/100 m)	PS-ACRF (dB/100 m)	Return Loss (dB)
1	2.0	70	67	68	65	78	75	21
4	3.6	62	59	58	55	70	67	29
10	5.7	55	52	50	47	52	49	30
16	7.7	55	52	45	42	50	47	30
31.2	11.2	48	45	40	37	35	32	29
62.5	16.4	48	45	30	27	35	32	27
100	20.9	40	37	20	17	30	27	27
200	27.3	35	32	10	7	20	17	20