



Class A+



ÖREN HD 113 PE

RG 6 U/4 (Cu/CuSn) Trishield PE

Kullanım Alanları

RG 6 tipi kablolar; Kablo TV (CATV), merkezi uydu anten sistemlerinde (SMATV) ve kablo internet gibi multimedia şebekelerinde kullanılmak üzere özel dizayn edilmiştir. Mobil iletişim uygulamalarında ortaya çıkan elektriksel gürültünün TV ve internet şebekelerinde yarattığı parazitini önüne geçilmesi için A+ sınıfı ekranlamaya sahip olan bu kablolar düşük zayıflama değerlerine sahip olup harici ortamlarda kullanıma uygundur.

Kablo Yapısı

İç İletken	Ø 1.13 mm Elektrolitik Bakır
İzolasyon	Ø 4.80 mm Fiziksel Köpüklü Skin/Foam/Skin PE
1. Ekran	Alüminyum Folyo (İzoleye Yapışık)
2. Ekran	Kalaylı Bakır Tellerden Örgü
3. Ekran	Alüminyum Folyo (Kılıfa Yapışık)
Dış Kılıf	Ø 6.80 mm PE

Teknik Özellikler

Kablo Ağırlığı	46 kg/km
Bakır Ağırlığı	21 kg/km
Min. Bük. Yarı Çapı	50 mm
Maks. Gergi Kuvveti	80 N
Çalışma Sıcaklığı	-40 °C ... +70 °C
Ambalaj	100 / 300 / 500 m

Elektriksel Özellikler

Empedans	75 ± 2 Ω
Kapasitans	53 ± 2 pF/m
Yayımlama Hızı	% 84
Yalıtım Direnci	> 2 GΩxkm
Çalışma Voltajı	1300 V
Test Voltajı	3000 V
İç İletken Direnci	< 17.80 Ω/km

Zayıflamalar (20°C)

5 MHz	1.40 dB/100m
50 MHz	4.10 dB/100m
230 MHz	8.20 dB/100m
470 MHz	12.30 dB/100m
860 MHz	16.90 dB/100m
1000 MHz	19.20 dB/100m
1200 MHz	21.90 dB/100m
2150 MHz	29.90 dB/100m
3000 MHz	36.20 dB/100m

Geri Dönüş Kaybı (20°C)

5-470 MHz	> 30 dB
470-1200 MHz	> 25 dB
1200-2000 MHz	> 23 dB
2000-3000 MHz	> 18 dB

Transfer Empedansı

5-30 MHz	≤ 1.5 mΩ/m
----------	------------

Ekranlama Zayıflaması

30-1200 MHz	≥ 110 dB
1200-2000 MHz	≥ 95 dB
2000-3000 MHz	≥ 85 dB

Standartlar

Ekranlama Sınıfı	Class A+
EN 50117-2-5	

CPR Sınıfı

F_{ca}

Application

This RG 6 type cable is specifically designed for use in multimedia networks and complies with screening of class A+ level, which is the high demand of Cable Network Operators. It has characteristics such as low loss, high screening efficiency, and high resistance to aging. It is suitable for outdoor usage.

Cable Construction

Inner Conductor	Ø 1.13 mm Bare Copper
Insulation	Ø 4.80 mm Gas Injected Skin/Foam/Skin PE
1st Shielding	Aluminum Foil (Bonded to the Insulation)
2nd Shielding	Tinned Copper Wire Braiding
3rd Shielding	Aluminum Foil (Bonded to the Jacket)
Outer Sheath	Ø 6.80 mm PE

Technical Properties

Cable Weight	46 kg/km
Copper Weight	21 kg/km
Min. Bending Radius	50 mm
Max. Tensile Strength	80 N
Temperature Range	-40 °C ... +70 °C
Packing	100 / 300 / 500 m

Electrical Properties

Impedance	75 ± 2 Ω
Capacitance	53 ± 2 pF/m
Velocity of Propagation	84 %
Insulation Resistance	> 2 GΩxkm
Operating Voltage	1300 V
Test Voltage	3000 V
Inner Conductor DCR	< 17.80 Ω/km

Attenuations (20°C)

5 MHz	1.40 dB/100m
50 MHz	4.10 dB/100m
230 MHz	8.20 dB/100m
470 MHz	12.30 dB/100m
860 MHz	16.90 dB/100m
1000 MHz	19.20 dB/100m
1200 MHz	21.90 dB/100m
2150 MHz	29.90 dB/100m
3000 MHz	36.20 dB/100m

Return Loss (20°C)

5-470 MHz	> 30 dB
470-1200 MHz	> 25 dB
1200-2000 MHz	> 23 dB
2000-3000 MHz	> 18 dB

Transfer Impedance

5-30 MHz	≤ 1.5 mΩ/m
----------	------------

Screening Attenuation

30-1200 MHz	≥ 110 dB
1200-2000 MHz	≥ 95 dB
2000-3000 MHz	≥ 85 dB

Standards

Screening Class	Class A+
EN 50117-2-5	

Euro Class

F_{ca}