



## EC1200 CAT 7A S/FTP



### Application

10Base-T, 100Base-T, 1000Base-T, 10GBase-T, and Fibredbus systems. Applicable for Power over Ethernet PoE / PoE+

### Cable Construction

- 22 AWG Bare Copper
- Skin/Foam/Skin PE Insulation
- Al-Pet Foil 100% Coverage
- Tinned Copper Wire Braiding
- Ø 7.90 mm ± 0.20
- LSZH or PE Jacket

### Standards

EIA/TIA-568  
ISO/IEC 11801 Class F  
IEC 61156-5, EN 50173-1  
EN 50288-4-1

### Technical Properties

Copper Weight	30 kg/km
Min. Bending radius during draw in	62 mm
Min. Bending radius permanently installed	32 mm
Max. Tensile Strength	95 N
Min. Crush Resistance	1000 N/10 cm
Min. Impact	10 Impacts
Installation Temperature	0°C ... +50°C
Operating Temperature	-20°C ... +70°C
Packing	305 / 500 m

### Electrical Properties

Max. Conductor Resistance	< 9.5 Ω / km
Max. Resistance Unbalance	< 2%
Min. Insulation Resistance	5000 MΩ x m
Mutual Capacitance	< 56 pF / m
Capacitance Unbalance	1600 pF / km
Impedance at 100 MHz	100 ± 5 Ω
Velocity of Propagation	76 %
Delay Skew	< 25 ns / 100 m
Coupling Attenuation	> 85 dB
Segregation Class	D
Transfer Impedance at 1/10/30 MHz	< 10/10/30 mΩ/m
Test Voltage	1000 V
Operating Voltage	125 V

### Electrical Data (Nominal)

@ 20 °C

Frequency (MHz)	Attenuation (dB/100 m)	NEXT (dB)	PS - NEXT (dB)	ACR (dB/100 m)	PS-ACR (dB/100 m)	ACRF (dB/100 m)	PS-ACRF (dB/100 m)	Return Loss (dB)
1	1.9	101	101	99	96	101	98	24
4	3.2	101	101	97	94	98	95	30
10	4.9	98	98	95	92	98	95	32
100	17.2	97	97	82	79	84	81	34
250	28.0	93	92	63	60	70	67	27
500	41.5	95	92	56	53	61	58	24
600	43.7	88	85	45	42	59	56	22
800	53.2	84	81	30	27	52	49	20
1000	55.4	83	80	28	25	50	47	19
1200	57.0	80	77	23	20	49	46	18

Product Name	Euro Class (CPR)	Flame Retardancy	Corrosive Gases Test	Smoke Density	Cable Weight
EC1200 Cat 7A S/FTP LSZH B <sub>ca</sub>	B <sub>ca</sub>	EN 60332-1-2	EN 50267-2-3	EN 61034-2	72
EC1200 Cat 7A S/FTP LSZH C <sub>ca</sub>	C <sub>ca</sub>	EN 60332-1-2	EN 50267-2-3	EN 61034-2	72
EC1200 Cat 7A S/FTP LSZH D <sub>ca</sub>	D <sub>ca</sub>	EN 60332-1-2	EN 50267-2-3	EN 61034-2	72
EC1200 Cat 7A S/FTP LSZH E <sub>ca</sub>	E <sub>ca</sub>	EN 60332-1-2	EN 50267-2-3	EN 61034-2	72
EC1200 Cat 7A S/FTP PE F <sub>ca</sub>	F <sub>ca</sub>	N/A	N/A	N/A	63